I claim:

1. A storage device having a lateral storage director, comprising:

5   at least one storage medium;

at least one recording transducer capable of recording data on said storage medium and reading data from said medium;

a storage device controller to control reading data

10   from said storage medium and writing data to said storage medium;

wherein said lateral storage director has a capability of communicating with the storage device controller, said lateral storage director is coupled with a communication

15   link, and said lateral storage director has a capability of communicating with a lateral storage director of another storage device via said communication link.

2. A storage device having a lateral storage director as in claim 1 wherein said lateral storage director includes a

20   communications link address which may be used to accept a query by a lateral storage director of another disk drive.

3. A storage device having a lateral storage director as in claim 1 wherein said lateral storage director includes a data file table.

4. A storage device having a lateral storage director as in claim 1 wherein said lateral storage director has the capability of determining the available storage space of the storage device.

5. A storage device having a lateral storage director as in claim 1 wherein said lateral storage director is capable of monitoring a performance parameter.

6. A storage device having a lateral storage director as in claim 1 wherein said storage device is a disk drive.

7. A storage device having a lateral storage director as in claim 1 wherein said storage device is a tape drive.

8. A storage device having a lateral storage director as in claim 1 wherein said storage device is a optical drive.

9. A method of moving data files from a first storage device having a lateral storage director directly to a

second storage device having a lateral storage director via a communications link comprising:

monitoring a performance parameter in said first storage device;

directly querying said lateral storage director of said second storage device for available storage space upon receiving an interrupt request in first said storage device;

transferring at least one data file from said first storage device to said second storage device; and,

updating the data file tables of the lateral storage director of said first storage device and said lateral storage director of said second storage device.

10. A method as in claim 9 wherein a host is coupled with said communications link and said host is notified when there is not sufficient available space to store the data file.

11. A method as in claim 9 wherein the storage space in said first storage device is released.

12. A method as in claim 9 wherein the performance parameter is an available space indicator of the storage device.

13. A method as in claim 9 wherein the performance parameter is a predictive failure indicator.

14. A method as in claim 9 wherein the performance parameter is the servo duty cycle.

15. A method as in claim 9 wherein the performance parameter is the routine actuator traffic.

16. A method as in claim 9 wherein the storage device is a disk drive.

17. A method as in claim 9 wherein the storage device is a tape drive.

18. A method as in claim 9 wherein the storage device is a optical drive.

19. A method of moving data files from a first storage device having a lateral storage director directly to a second storage device via a communications link comprising:

monitoring a performance parameter in said first storage device;

entering a host emulation mode; and,

transferring at least one data file from said first
storage device to said second storage device.

20.   A method of initializing a first storage device having
a lateral storage director, comprising:

sending a query using an address resolution protocol
from said first storage device connected with a
communications link;

receiving a reversed address resolution protocol from
at least one second storage device;

compiling a list of addresses in use; and,

self-assigning an unused address.

21.   A method as in claim 20 wherein the list of addresses
are stored temporarily in a lateral storage director portion
of read only memory.